Century MP Access

High Efficiency Traction Chargers Century MP Access 80V 100A CG5113

Century MP Access is the next generation of chargers. Incorporating a specialised charging algorithm, high efficiency power conversion and integrated queuing facilities, the MP Access is industry leading.

The microprocessor using a Century specified algorithm can optimise charging on a range of battery types. This optimisation has the benefit of delivering a fully charged battery quicker while minimising the effects that standard chargers can have on batteries.

The use of high frequency power conversion has the effect of reducing the amount of energy consumed for charging, and providing a greater level of control of the power output. This technology also has the advantage of being lighter weight to conventional thyristor controlled chargers. This allows operators to have the option of wall mounting these chargers, reducing the possible risk of impact from other equipment, and improving the use of space.

The integrated queuing facility provides a simple and effective method of monitoring and then identifying which of the batteries being charged has reached the higheststate-of-charge. This has the facility to increase the lifeof batteries and improve the efficiency of operations.



Features and Benefits

- Queuing battery system: Facility to increase the life of the battery and run time of electrical materials handling equipment.
- Century approved charging algorithms: Century specified charging profiles to improve charging efficiency and reduce physical wear on the battery, such as increase water consumption.
- Programmed charge time: Provides the option to operators to charge batteries when electricity tariff is lower to further help reduce consumption of electricity at peak rates.

- Alarm indicators: Highlights to the operator and logs issues with the charger and battery.
- High frequency power conversion: With >91% efficiency with power conversion from input power to output power, can have the advantage of reducing the amount of power consumed to recharge batteries.





Century MP Access

Century MP Access 80V 100A CG5113


ELECTRICAL INPUT SPECIFICATIONS		
3P 400Vac ±10%		
15.5A (@400VAC)		
47-63Hz		
56C420		
0.95 at rated power		
94% at rated power		


ELECTRICAL OUTPUT SPECIFICATIONS		
	High Frequency Conversion(Soft Start)	
Nominal VDC (Programmable)	24VDC; 36VDC; 48VDC; 72VDC and 80VDC	
VDC Output Range	1.4 to 2.9VDC per cell	
Output Power (kW)	9.6kW (2.4VPC @400VAC)	
Max Output Current (A)	100A	
Output Ripple	<5% RMS of Nominal DC Voltage &	
	<10% RMS ripple current at 100% load	
Output Accuracy Setting	VDC output $\pm 0.5\%$ / Current output $\pm 2\%$	

ENVIRONMENTAL SPECIFICATIONS		
Environmental Protection	Conformal coating	
Operational Temperature (Ambient)	0 - 40 °C	
Storage Temperature	-25 - 60 °C	
Humidity	RH <95% Non-condensing	
Cooling	Fan cooled	
IP Rating	IP20	

STANDARDS	
Emissions	EN61000-6-3
Immunity	EN61000-6-2
Safety	EN60335-1 & EN60335-2-29

MECHANICAL	
Weight (kg)	20kg
Height (mm)	417
Width (mm)	256
Depth (mm)	243





An affiliated business of the GS Yuasa Corporation, Century Yuasa has over 80-years of supplying a range of stored energy solutions to the Australian market. An established network of sales and distribution offices throughout Australia and New Zealand has seen the business gain the trust and respect from its customers by focusing on quality products and exceptional customer service. The portfolio within Century Yuasa includes a wide range of stored energy products and services, as well as identifiable brands and unique technologies for automotive, materials handling and stationary power applications. Directly maintaining and operating two manufacturing centres in Australia and employing some 500 people, Century Yuasa continues the leading Australian manufacturer of stored energy products.